



SCANTECH ID[®]
CHAMPTEK Group

IG521/IG522

Wireless 2D Barcode Scanner

Introduction

IG521 or IG522 is a modern design, gun-type wireless 2D bar code scanner. Its wireless supports both 2.4G RF and Bluetooth, has most modern design, which is designed especially for retail, logistic, manufacturing, mobile payment, express delivery, inventory management, food traceability, asset inventory and warehousing management market. It can easily read the barcode on paper label, display screen and other media.

The product uses enhanced wireless 2.4G transmission technology, its 2.4G RF wireless transmission, automatic frequency hopping and anti-interference, the effective transmission distance can reach 60 meters, while Bluetooth connection reaches 30 meters in open space. Its out of range or batch transmission mode with memory capacity stores up to 20,000 inputs of EAN13 barcodes.

IG521 or IG522 has good performance for the majority of 1D and 2D bar codes, Post code, Composite codes, and passport OCR-B character reading to increase your productivity. It can easily read the barcodes on label, display and other media.

It is a high performance barcode scanner which provides customers with the most cost-effective solution in the market.

Features

- Support most 1D, 2D, GS1 Databar codes, post code, composite codes and passport OCR-B.
- Good performance on both display and printed label reading.
- Communication Interface : USB wired, wireless 2.4G and Bluetooth 4.2.
- 2.4G RF wireless transmission, automatic frequency hopping and anti-interference, the effective transmission distance in open space can reach ≥ 60 meters. With Bluetooth 4.2 connection reach up to 30m in open space.
- IG521 scanner is built in both 2.4G RF and Bluetooth, equipped with a type-A charge cable and a 2.4G RF receiver dongle.
IG522 scanner is built in both 2.4G RF and Bluetooth, equipped with a charge cradle and a 2.4G RF receiver dongle.



IG521/IG522

| Barcode | Depth of field |
|----------------------|----------------|
| 0.076mm/3mil Code39 | 80 ~ 190 mm |
| 0.1mm/4mil Code39 | 60 ~ 150 mm |
| 0.25mm/10mil Code39 | 80 ~ 420 mm |
| 0.5mm/20mil Code39 | 50 ~ 650 mm |
| 0.33mm/13mil UPC/EAN | 70 ~ 550mm |
| 20mil QR Code | 30 ~ 320 mm |
| 8mil Data Matrix | 40 ~ 135 mm |
| 8mil PDF417 | 20 ~ 200 mm |

The test is under ambient light 400 ~ 500 Lux.



IG521
(Equipped an USB type-B to type-A charge cable & a 2.4G RF receiver dongle)



IG522
(Equipped a charge cradle & a 2.4G RF receiver dongle)

Specifications

Physical Characteristics

| | |
|-----------------|---|
| Body Weight | 151g (Scanner) / 201g (Cradle) |
| Material | ABS |
| Dimension | L167 x W70 x H88mm (Scanner) L123 x W88.5 x H70 (Cradle) |
| Color Available | Black body, dark gray button and windows side |

Performance

| | |
|-------------------------------|---|
| Light Source | White light illumination, Red bar aimer |
| Sensor | 1280(H) x 1024(V) pixels |
| Field of view | Horizontal - 42°, Vertical - 35° |
| Motion tolerance | 65cm per second |
| Reading Distance | 650 mm@20mil/0.5mm, PCS90%, Code39 |
| Print Contrast Ratio(Minimum) | ≥15% |
| Resolution | 1D: ≥3mil/0.076mm PCS90%, CODE 39 2D: 7mil/0.18mm PCS90%, QRCode |
| Reading Angle | |
| Pitch Angle | ±5°~60° (±5°) |
| Skew Tolerance | ±5°~55° (±5°) |
| Method of Communication | 2.4G RF or Bluetooth (HID, SPP, BLE) |

Environmental

| | |
|-------------------|----------------------------------|
| Operating Temp. | -20°C to 50°C (-4°F to 122°F) |
| Storage Temp. | -40°C to 60°C (-40°F to 140°F) |
| Relative Humidity | 5% to 95% (Non-condensing) |
| Ambient light | 100,000 Lux Max. (Sunlight) |

Reliability

| | |
|--------------------|-----------------------|
| MTBF(Calculated) | 50,000 hours minimum |
| Cable Bending Test | 30 times/min@500g/90° |
| Drop | 150cm |

Power

| | |
|------------------|-------------------------------|
| Voltage Battery | Li-Ion 3.7V/2000mA |
| Recharge time | Approx. 5 hours (5V@1000mA) |
| Reads per charge | ≥ 12 hours in continuous read |

Radio Characteristics

| | |
|--------------------|--|
| Wireless Standard | 2.4GHZ (ISM frequency band) , Bluetooth 4.2 |
| Frequency Band | 2.402GHz~2.480GHz |
| Transmission Range | ≥ 60m line of sight for 2.4G RF, up to 30m for Bluetooth 4.2 |

Readable Symbologies

1D Symbologies

UPC-A,UPC-E,EAN-8,EAN-13,Code 128, GS1-128, Code 39,Code 32, Code 93,Code 11,Interleaved 2 of 5,Matrix 2 of 5,Industrial 2 of 5 (Straight 2 of 5),Standard 2 of 5 (IATA 2 of 5), Codabar (NW-7), MSI,GS1 Databar (Omnidirectional, Limited, Expanded),China Post, Telepen, Febraban,GS1 Composite

2D Symbologies

QR Code, Micro QR Code, Data Matrix, PDF417, Micro PDF 417, MaxiCode, Aztec, HanXin Code.

OCR character

OCR-B and Chinese ID Card OCR .

Due to Champtek/Scantech ID's continuing product improvement programs, specifications and features are subject to change.