

Rugged Tablet X-100



Versatile Overall Mobile Solution

Introduction

SCANTECH ID X-100 is a versatile rugged powerful tablet designed for diversified applications in self-service, ID identification, information service, multimedia service, and your customized interactive applications and services in every environment of retail, logistics, inventory, transportation, medical care, hospitality and office building. The strength of the X-100 comes from customizable optional feature modules within the IP65 reliable device. X-100 runs on open platforms such as Android, with low power consumption and long battery duration, and it is easy to implement customer application. For information about our OEM models and services, please contact our regional sales representative.

Features

- IP65 1.2m drop tested military grade tablet with 10.1" touch display
- Low power consumption and long battery life support up to 15 hours
- Physical RJ45 ethernet port and USB to Ethernet converter(optional)
- Dual MIC with voice tracking, background noise & echo cancellation
- High Security built-in MediaTek CryptoCore, TPM2.0 with FIPS 140-2
- Ergonomical shoulder strap allow long hour hands-free operation
- Adjustable Desktop Stand on product itself, no extra cradle needed

- Handy F1 quick access button to activate specific APP
- Rear camera 1D/2D Barcode Decoder
- RFID(NFC) module support (optional)
- 1-to-4 Battery Charger and Spare Battery (optional) 1to-8 Multiple Battery Charging Set (optional) Mobile
- IP55 Carry Case design including accessories Remote
- OTA system upgrade support

Rugged Tablet X-100

• Durability

Specifications

• System Architecture

Processor	MT8788(Octa Core), 2.0GHz x4+2.0GHz x4, Separated GPU (Mali-G72)
Operating Platform	Android 9.0 OS
Dimensions	283.30mm x 191.84mm x21.86mm [11.15" x 7.55" x 0.86"]
Weight	1420g [3.12 lbs]
Memory/Storage	(UMCP) 2GB+32GB / 8GB+256GB (max.)
Security	MTK CrytoCore (TPM2.0 with FIPS 140-2)
Modia	

Media

Display	10.1" WUXGA 1200x1920 IPS 550 nits 10-
	point multi-touch [Supports thin medical
	glove and wet-touch mode]
Speakers	2 integrated Speakers
Dual Microphones	Voice tracking, noise & echo cancellation

Network Interface •

Wired LAN	100/1000 Mbps-(Conforms with IEEE802.3x)
Wireless LAN	Wi-Fi 802.11 a/b/g/n/AC Bluetooth [®] 4.1
Wireless Bluetooth	GPS/Glonass/Beidou/Galileo/QZSS/SBAS
Wireless GPS	Tri-band reception concurrently

• 4G LTE Module Band Frequency

(4G)LTE FDD	B1/B3/B5/B8
(4G)LTE TDD	B34/B38/B39/B40/B41
(3G)WCDMA	B1/B5/B8
(2G)GSM	B3/B8 (900&1800)

• Scan Module (optional)

1D/2D Barcode scanner
2D Fingerprint scanner
RFID(NFC) module

Optional Accessories

SCANTECH ID

CHAMPTEK Group

Battery Maximum 1-to-8 Battery Charging

Durability	
Storage Temperature	-20°C ~ 70°C
Operating Temperature	-10°C ~ 60°C
IP Protection	IP65, 500 times x 1 m tumble test
Drop Resistance	MIL-STD-810G method 516.6 procedure
	IV 48"/1.2m drop pass, 26 times
	including all corners, edges and faces.
	IEC60068-2-31 handling shocks with
	50cm drop on six faces.
	Screen Protector Glass resists 64 gm
	steel ball drop from 120cm.
Power Supply	
AC Adapter	57W (19V / 3A)
Battery Volume	Swappable battery, integrated
	10800mAh battery pack
Battery Endurance	up to 12 hours
• I/O Ports	
	USB 3.0 x1 (TYPE C Port)
	USB 2.0 x1 (TYPE A Port)
	RJ45 Physical Ethernet Port
	DC jack
	3.5mm Audio jack
	SIM Card Slot
	Micro SDXC Card Slot(support up to 128G)
	Reset Hole
• Camera	
Camera Front	5MP
Camera Rear	8MP, with Auto Focus, Flash
Regulatory	
	CE, NRCS, RoHS Certifications
	ICASA TA-2020/5354





Heliumweg 34a 3812 RE Amersfoort, The Netherlands www.scantech-id.com

СНАМРТЕК ІNC.

1/F, No.4, Alley 2, Shih-Wei Lane, Chung-Cheng Rd., Xindian Dist., New Taipei City 231, Taiwan TEL: +886-2-2219-2385 FAX: +886-2-2219-2387 www.champtek.com