

## Rugged Tablet X-120



**Versatile Overall Mobile Solution** 

#### Introduction

SCANTECH ID X-120 is a versatile rugged powerful tablet designed for diversified applications in self-service, ID identification, information service, multimedia service, and your customized interactive applications and services in every environment of retail, logistics, inventory, transportation, medical care, hospitality and office building. The strength of the X-120 comes from customizable optional feature modules within the IP65 reliable device. X-120 runs on open platforms such as Android, with low power consumption and long battery duration, and it is easy to implement customer application. For information about our OEM models and services, please contact our regional sales representative.

#### Features

- IP65 1.2m drop tested military grade tablet with 10" touch display
- Low power consumption and long battery life more than 12 hours
- Dual MIC with voice tracking, background noise & echo cancellation
- High Security built-in MediaTek CryptoCore, TPM2.0 with FIPS 140-2
- Ergonomical shoulder strap allow long hour hands-free operation
- Adjustable Desktop Stand on product itself

- Handy F1 quick access button to activate specific APP
- Rear camera 1D/2D Barcode Decoder
- RFID(NFC) module support (optional)
- 1-to-4 Battery Charger and Spare Battery (optional)
- IP55 Carry Case design including accessories
- Remote OTA system upgrade support

# **Rugged Tablet X-120**

### **Spec**ifications

#### • System Architecture

•	
Processor	MT8788(Octa Core), 2.0GHz x4+2.0GHz x4, Separated GPU (Mali-G72)
<b>Operating Platform</b>	Android 11 OS
Dimensions	259.50mm x 171.6mm x19mm [10.22" x 6.76" x 0.75"]
Weight	1420g [3.12 lbs]
Memory/Storage	(UMCP) 4GB+128GB / 8GB+256GB (max.)
Security	MTK CrytoCore (TPM2.0 with FIPS 140-2)
• Media	
Display	10" WUXGA 1920x1200 IPS 550 nits 10- point multi-touch
Speakers	2 *8 Ohm 1W
Dual Microphones	Voice tracking, noise & echo cancellation
Network Interface	

#### 

Wired LAN	100/1000 Mbps-(Conforms with IEEE802.3x)
Wireless LAN	Wi-Fi 802.11 a/b/g/n/AC
Wireless Bluetooth	Dual Frequevery (EDR+BLE 4.0)
Wireless GPS	GPS/Glonass/Beidou/Galileo/QZSS/SBAS
	Tri-band reception concurrently

#### • 4G LTE Module Band Frequency

(4G)LTE FDD	B1/B3/B5/B8	
(4G)LTE TDD	B34/B38/B39/B40/B41	
(3G)WCDMA	B1/B5/B8	
(2G)GSM	B3/B8 (900&1800)	

#### • Scan Module (optional)

1D/2D Barcode scanner
2D Fingerprint scanner
RFID(NFC) module

#### • Durability

<b>_</b>	Durability			
	Storage Temperature	-20°C ~ 70°C		
	<b>Operating Temperature</b>	-10°C ~ 60°C		
	IP Protection	IP65		
	Drop Resistance Power Supply	500 times x 1 m tumble test MIL-STD-810G method 516.6 procedure IV 48"/1.2m drop pass, 26 times including all corners, edges and faces. IEC60068-2-31 handling shocks with 50cm drop on six faces. Screen Protector Glass resists 64 gm steel ball drop from 120cm.		
	AC Adapter	57W (19V / 3A)		
	Battery Volume	Swappable battery, integrated 12000mAh battery pack		
	Battery Endurance	12 hours		
• I/O Ports				
		USB TYPE-C (1*USB2.0 OTG)		
		USB TYPE-A (2*USB2.0)		
		DC jack		
		SIM Card Slot		
		Micro SDXC Card Slot(support up to 128G)		
	Camera			
	Camera Front	8 MP		
	Camera Rear	13 MP, with Auto Focus, Flash		
	Optional Accessories			
		1 to 4 Battery Charging cradle		
	Regulatory	X-120: CE, RoHS, MIL-STD 810G, 3C		



Description of Product Appearance and Functions

Battery: UN38.3, IEC62133, MSDS



Size (no corner cushion ): 259.5MM \* 171.6 MM \* 20.50MM Size (with corner cushion): 268.5MM \* 180.6MM \* 25.95MM

#### SCANTECH-ID BV

Heliumweg 34a 3812 RE Amersfoort, The Netherlands TEL: +31 (0) 33 4698400 FAX: +31 (0) 33 4650615 www.scantech-id.com CHAMPTEK INC.

1/F, No.4, Alley 2, Shih-Wei Lane, Chung-Cheng Rd., Xindian Dist., New Taipei City 231, Taiwan TEL: +886-2-2219-2385 FAX: +886-2-2219-2387 www.champtek.com