



# IG752

## Wireless DPM Barcode Scanner

### Introduction


IG752 is a high performance wireless industrial handheld 2D and DPM barcode scanner.

It utilizes advanced CMOS imaging recognition technology and an intelligent image recognition system, equipped with 1.3 million pixel global exposure camera, which effectively handles barcodes with dirt, defects, and low contrast. It is mainly used in DPM barcode scanning in industrial production, machinery manufacturing, PCB production and other scenarios.


It has most modern design with rugged casing and supports IP54 sealing protection, features enhanced wireless 2.4G RF and Bluetooth transmission technologies, with an effective range of over 60 meters in open outdoor environments. With its unmatched performance for the majority of 1D, 2D and DPM barcode reading to increase your productivity.

### Features

- It is anti-drop and anti-vibration with highly integrated 2D decoding structure.
- Its high-performance MCU to easily identify the mainstream 1D, 2D and DPM barcodes in the market.
- Built in 1.3 megapixel global exposure camera that has excellent performance in reading 3mil and DPM codes in reflection, low contrast, perforation, distortion, corrosion on plastic, cast iron, PCB, aluminum and other types of DPM materials with processes such as drilling, laser printing, mechanical impact, etching.
- Enhanced wireless 2.4G RF transmission technology, with a reliable outdoor transmission range of over 60 meters.
- Supports synchronous mode (scan and transmit immediately) and storage mode, capable of storing over 20,000 EAN13 product codes.
- Communication configuration (1) Scanner to cradle via wireless 2.4G RF, cradle to PC host is via a wired USB cable (setup as USB-KBW or USB-COM) or (2) Scanner to PC/host via Bluetooth 4.2, cradle is for charging.
- Vibration feedback for clearer scanning.



Drilling DPM



Laser printing



Mechanical impact








Etching

# IG752

**Mechanical Drawing**  
Unit: mm

## Depth of Field

Barcode Type	Barcode Density	Minimum	Maximum
Code 39	0.076mm(3mil)	40mm	75mm
Code 39	0.127mm(5mil)	30mm	90mm
Data Matrix	0.127mm(5mil)	40mm	70mm



## Specifications

### Physical Characteristics

Weight	Scanner approx. 228g (incl. Battery)
Cable Length	1.5 meters
Dimension	Scanner : 75.00(W) x 171.31(H) x 82.85mm(L) Cradle : 112.18(W) x 84.64(H) x 130.60mm(L)
Color	Black or Beige

### Performance

Light Source	White light illumination, Red bar aimer
Sensor	1.3m / 1280*1024 pixels
Field of view	Horizontal – 40°, Vertical – 34°
Scan Speed	65 cm per second
Reading Distance	450mm@20mil/0.5mm, PCS90%, QRCode
Print Contrast Ratio	≥20%
Resolution	1D: 3mil/0.076mm PCS90%, Code39 2D: 5mil/0.127mm PCS90%, DM code
Scanning Mode	Trigger, Induction, Continuous
Indicator	LED, Buzzer, Vibrator
Storage Capacity	350KB (over 20,000 EAN13 codes)
Communication Mode	Synchronous or Storage mode
Reading Angle	
Pitch Angle	5°~60° (±5°)
Skew Tolerance	5°~60° (±5°)
Rolling	±360°
Ambient Light	Dark Environment, Indoor Natural Light
Sealing	IP54 Water and dust protection

### Power

Voltage Battery	Li-Ion 3.7V/2600mAh
Recharge time	Approx. 5 hours (5V@1000mA)
Reads per charge	20,000Times in continuous read

### Radio Characteristics

Wireless Standard	2.4GHZ (ISM frequency band) , Bluetooth 4.2
Frequency Band	2.402GHz~2.480GHz
Transmission Range	≥= 60m line of sight for 2.4G RF to cradle, up to 30m for Bluetooth 4.2 to host device

### Environmental

Operating Temperature	-20 °C to 50 °C (-4 °F to 122 °F)
Storage Temperature	-40 °C to 70 °C (-40°F to 158 °F)
Relative Humidity	5% to 95% (Non-condensing)
Vibration Test	10H@125RPM

### Reliability

Life Time	
Trigger Switch	1,000,000 times @1kg ±50g cycles
MTBF (calculated)	50,000 hours
Thermal Shock	
High Temp.	60 °C (140 °F)
Low Temp.	-20 °C (-4 °F)
Cycle time	30 minutes for high temp. , 30 minutes for low temp.
Cycles	24 cycles
Cable Bending Test	25,000 times minimum (30 times/min @ 200g/90°)
Drop Resistance	59.05 inches (150cm) drop on concrete surface

### Readable Symbolologies

#### Code Symbolologies

1D : UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Interleaved 2 of 5.  
2D: QR Code, Data Matrix, Micro QR Code , Aztec Code, Hanxin Code.

#### Good performance to read DPM barcode

Due to Champtek/Scantech ID's continuing product improvement programs, specifications and features are subject to change.